



HAWAII FLOOR COVERING

| | |
|---|--|
| classificazione al fuoco resistance against fire clasificación al fuego classement feu | Efl |
| composizione - composition composición - composition | 3000/1 dtex PP fibrillato riccio 3000/1 dtex PP fibrillated curled |
| fondo - backing soporte - dossier | lattice - latex látex - latex |
| spessore totale - total height espesor total - épaisseur total | 7 mm (+/- 10%) |
| peso fibra - pile weight peso fibra - poids fibre | 480 g/m ² (+/- 10%) |
| peso totale - total weight peso total - poids total | 1.140 g/m ² (+/- 10%) |
| numero punti/m ² number of knots/m ² número de puntos/m ² nombre de points/m ² | 91.350/ m ² (+/- 10%) |
| solidità alla luce - lightfastness resistencia a la luz - solidité à la lumière | xenon test: scala di blu > 7 / scala di grigi >4 xenon test: blue-scale > 7 / grey-scale >4 |
| dimensione pezze - size of the rolls medida piezas - dimension des pièces | ml 20/25 ca. x h. cm 200/400 |
| colori - colours colores - coloris | 3 |
| destinazione use utilización utilisation | balconi, piscine, solarium, terrazze, altre superfici esterne balconies, swimming pools, solariums, terraces, other external surfaces balcones, piscinas, solariums, azoteas, otras superficies exteriores balcons, piscines, solariums, terrasses, autres surfaces extérieures |



bianco



rosso



nero