



YUCON

FLOOR COVERING

tipo produzione manufacturing process método de fabricación méthode de fabrication	agugliato needlefelt punzonada aiguilleté
composizione - composition composición - composition	100% PP
fondo - backing soporte - dossier	schiuma gel gofrato - wafel backing espuma gel gofrado - mousse de gel gaufré
peso filato - pile weight peso fibra - poids poil	1.700 g/m ²
peso totale - total weight peso total - poids total	2.770 g/m ² +/-15%
spessore fibra - pile height espesor pelo - épaisseur poil	5,5 mm
spessore totale - total height espesor total - épaisseur total	11 mm
lunghezza rotoli size of the rolls medida piezas dimension des pièces	23 ml
altezza rotoli - width ancho - largeur	100/200 rotoli o taglio - rolls or cut rollos o corte - rouleaux ou coupe
destinazione use utilización utilisation	EN 685 classe d'uso: 23, traffico medio, ingressi, locali pubblici, abitazioni EN 685 use class: 23, medium traffic, entrances, public buildings, houses EN 685 clase de utilización: 23, medio tráfico, entradas, locales públicos, viviendas EN 685 classe d'utilisation: 23, trafic moyen, entrées, locaux publics, habitations



ENTRANCE

Ci riserviamo il diritto di apportare ai nostri prodotti, senza preavviso, ogni modifica necessaria
Montecolino S.p.A. reserves to itself to make any variations
Nous nous réservons le droit d'apporter à nos produits, sans préavis, toute modification nécessaire
Nos reservamos el derecho de modificar nuestros productos, sin previo aviso